



UN?BEARINGS(UK)LTD.



32006jr Bearing 2D drawings and 3D CAD models

Koyo Hot Sale and Durable 32006jr Metric Tapered Roller Bearing 32007jr Automobile Bearing

Bearing No. 32006jr

| | |
|-------------------------------|-------------|
| Size | 30x55x17 mm |
| Bore Diameter | 30 mm |
| Outer Diameter | 55 mm |
| Width | 17 mm |
| d | 30 mm |
| D | 55 mm |
| T | 17 mm |
| B | 17 mm |
| C | 13 mm |
| a | 13,6 mm |
| r min. | 1 mm |
| r2 min. | 1 mm |
| da min. | 35,5 mm |
| da max | 35 mm |
| Da min | 47 mm |
| Da max. | 49,5 mm |
| Db min. | 52 mm |
| ra max. | 1 mm |
| rb max. | 1 mm |
| Weight | 0,177 Kg |
| Basic dynamic load rating (C) | 38,2 kN |
| Basic static load rating (C0) | 48 kN |
| (Grease) Lubrication Speed | 7000 r/min |
| (Oil) Lubrication Speed | 9400 r/min |



UN?BEARINGS(UK)LTD.

| | |
|--------------------------|--|
| Calculation factor (e) | 0,43 |
| Calculation factor (Y0) | 0,77 |
| Category | Tapered Roller Bearing Assemblies |
| Inventory | 0.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.18 |
| EAN | 0605790123542 |
| Product Group | B04334 |
| Precision Class | Standard |
| Component | Assembly |
| Basic Number | 32006 |
| Number of Tapered Rows | Single Row |
| Inch - Metric | Metric |
| Other Features | High Load Capacity |
| Long Description | Assembly; Standard Precision; 30MM Bore; 55MM Outside Diameter; 17MM Assembly Width; Single Row of Rollers |
| Category | Tapered Roller Bearings Assembly |
| UNSPSC | 31171516 |
| Harmonized Tariff Code | 8482.20.00.00 |
| Noun | Bearing |
| Keyword String | Tapered |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 32006JR |
| Weight / LBS | 0.39 |
| Assembly Width | 0.669 Inch 17 Millimeter |
| Flange Outside Diameter | 0 Inch 0 Millimeter |
| Bore | 1.181 Inch 30 Millimeter |
| Outside Diameter | 2.165 Inch 55 Millimeter |
| | |



UN?BEARINGS(UK)LTD.

| | |
|------------------|---------|
| Bearing No. | 32006JR |
| r(min) | 1 |
| r1(min) | 1 |
| Cr | 47.9 |
| C0r | 48.0 |
| Cu | 6.75 |
| Grease lub. | 7000 |
| Oil lub. | 9400 |
| a | 13.6 mm |
| da(min) | 35.5 |
| db(max) | 35 |
| Da(max) | 49.5 |
| Da(min) | 47 |
| Db(min) | 52 |
| Sa(min) | 3 |
| Sb(min) | 4 |
| ra(max) | 1 |
| rb(max) | 1 |
| e | 0.43 |
| Y1 | 1.39 |
| Y0 | 0.77 |
| (Refer.)Mass(kg) | 0.177 |